

- Robust housing with Hardox lining and wear strips
- Screw conveyor and cross-feed conveyor channel made of wear-free Hardox
- Can be attached to mowing crane with hydraulic ring mount and quick release
- · Flail shaft can be equipped with Y-blade or forestry flail
- · Mulcher with or without suction, guided by ring mount
- For shrubbery and woody plants up to max. 15 mm
- · Adapted to the requirements for working on track embankments
- · Maintenance-friendly design
- Tested version with stone guard seal
- Design and configuration as an eco mower


## **Cover picture**


- · Suction mower MTSM 1200 on Unimog equipment carrier
- · With telescopic mowing crane and powerful blower
- · Mowing width 1200 mm





## Technical data

Manufacturer	Müller Technologie AG
Cutting width	1200 mm
Cutting tool	Y-blade
Drive power - flail shaft	40 kW
Pressure / volume flow rotor shaft	280 bar / 80 l/min
Cut material conveyor	Ejection screw
Drive power - screw mechanism	13.4 kW
Pressure / volume flow screw shaft	210 bar / 37 l/min
Weight	430 kg
Dimensions WxHxD	1450 x 815 x 1090 mm
Height of bottom mounting plate	740 mm (with a cutting height of 120 mm)









**Adrian Meier**Product manager
Municipal technology

Telefon +41 52 557 92 29 a.meier@rte.ch

Your contact

## Müller Technologie AG

a subsidiary of Müller Frauenfeld AG Langfeldstrasse 94 8500 Frauenfeld

www.mueller-frauenfeld.ch